

1/2 - (C) EPODOC / EPO

PN - DE29802064U U 19980402
PR - DE19982002064U 19980206
AP - DE19982002064U 19980206
DT - *
EC - D03C3/12 ; D03C3/42
IC - D03C3/42 ; D03C3/12
PA - GROSSE WEBEREIMASCHINEN GMBH (DE)

2/2 - (C) EPODOC / EPO

PN - FR2648159 A 19901214
PNFP- FR2648159 B 19930507
PR - DD19890329498 19890612
AP - FR19900007219 19900611
DT - *
CT - EP0280132 A [AD]; EP0106974 A [A]; GB883257 A [A];
BE529019 A [A]; DE3524569 A [A]; FR2587046 A [AD]
EC - D03C3/12 ; D03C3/20
IC - D03C3/12
IN - HEIDE ANDREAS; GOESSL RAINER; HAHN KARL-HEINZ
INFP- NO CHANGE
PA - TEXTIMA VEB K (DD)
PAFP- NO CHANGE

TI - Control of lifting hooks in an open shed Jacquard knitting machine of a loom for weaving pile fabric (plush) in particular weaving loom for ingrain carpets

AB - Two lifting hooks 4 to 11 contiguous in the direction of passage of the cloth, from the field of front lifting hooks 2 and from the field of rear lifting hooks 3 of a first group of upper lifting hooks 1 are joined together by the upper pulley 36 to 39 of a first multiple pulley 40 to 43 with a pull cable 32 to 35, and each lifting hook 4 to 11 with an associated electromagnet 28 to 31 may be blocked with respect to the displacement of the associated blades 20 to 26, 88 to 90; over the lower pulley 44 to 47 of two upper multiple pulleys 40 to 43 which are contiguous in the direction of passage of the cloth there passes a pull cable 48 to 51 the first end of which is fixed to a heald eyelet 54 to 57 and the second end of which is fixed to a frame 52, 53 which can be raised and lowered and which extends as a single piece or a two-part embodiment, over the width of the machine.

<IMAGE>

PLASTICS MATERIAL BEND FLEXIBLE TUBE FIX PERFORATION CONTAIN SOAP

IN - DUGAY D

PA - (DUGA-I) DUGAY D

PN - FR2648169 A 19901214 DW199106 000pp

ORD - 1990-12-14

IC - E03D9/02

FS - GMPI

DC - Q42

AB - FR2648169 The device is for diffusing a disinfecting and coloring prod, in the water of a WC. It is in the shape of a disc or flower made from plastic or any other material on which a flexible plastics tube is fixed. The tube has a bent part with perforations and in its central part, there are cylinders of soap, as well as perforations in the bottom part.

- This allows the diffusion of the soap in the water thanks to a regulator ring sliding on the end of the tube. The disc or flower shaped part may contain deodorant which can be in a small block on each petal.

- **ADVANTAGE** - Does not require cistern top to be removed.(8pp Dwg.No, 2/3)